



INTEGREX i-500s

Specification		Bed Length - 1500U mm	Bed Length - 2500U mm	Bed Length - 3000U mm
Capacity	Maximum Swing	700 mm	700 mm	700 mm
	Maximum Machining Diameter	700 mm	700 mm	700 mm
	Maximum Machining Length	1574 mm	2594 mm	3074 mm
Main Spindle	Maximum Speed	4000 rpm	4000 rpm	4000 rpm
	Motor Output (40 ED Rating)	30 kw / 40 hp	30 kw / 40 hp	30 kw / 40 hp
Second Spindle	Maximum Speed	4000 rpm	4000 rpm	4000 rpm
	Motor Output (40 ED Rating)	30 kw / 40 hp	30 kw / 40 hp	30 kw / 40 hp
Milling Spindle	B-Axis Travel	240°	240°	240°
	Magazine Capacity	36	36	36
	Maximum Speed	12000 rpm	12000 rpm	12000 rpm
	Motor Output (40 ED Rating)	24 kw / 32 hp	24 kw / 32 hp	24 kw / 32 hp
Feed Axes	Travel (X Axis)	845 mm	845 mm	845 mm
	Travel (Y Axis)	430 mm	430 mm	430 mm
	Travel (Z Axis)	1640 mm	2660 mm	3140 mm