

## **INTEGREX J-300**

The INTEGREX j-300 effectively provides ease of operation, high accuracy and higher productivity for a reasonable investment.

| Specification   |                             | Bed Length - 650 mm | Bed Length - 1200 mm |
|-----------------|-----------------------------|---------------------|----------------------|
| Capacity        | Maximum Swing               | 640 mm              | 640 mm               |
|                 | Maximum Machining Diameter  | 500 mm              | 500 mm               |
|                 | Maximum Bar Work Capacity   | 80 mm               | 80 mm                |
|                 | Maximum Machining Length    | 629 mm              | 1165 mm              |
| Main Spindle    | Chuck Size                  | 10 in               | 10 in                |
|                 | Maximum Speed               | 4000 rpm            | 4000 rpm             |
|                 | Motor Output (40 ED Rating) | 19 kw / 25 hp       | 19 kw / 25 hp        |
| Milling Spindle | B-Axis Travel               | 220°                | 220°                 |
|                 | Magazine Capacity           | 20                  | 20                   |
|                 | Maximum Speed               | 12000 rpm           | 12000 rpm            |
|                 | Motor Output (40 ED Rating) | 22 kw / 30 hp       | 22 kw / 30 hp        |
| Feed Axes       | Travel (X Axis)             | 615 mm              | 615 mm               |
|                 | Travel (Y Axis)             | 260 mm              | 260 mm               |
|                 | Travel (Z Axis)             | 695 mm              | 1231 mm              |
|                 | Travel (W Axis)             | 632 mm              | 1190 mm              |

