

MULTIPLEX W-200Y

Capacity	Max. machining diameter	Φ13 "
	Max. machining length	7 "
Spindle	Chuck size	8 "
	Max. spindle speed	5000 rpm
	Max. torque (25%ED)	344 ft-lbs
	Spindle motor (40%ED)	22 kW (30 HP)
	Spindle motor (cont. rating)	15 kW (20 HP)
	Chuck size	8 "
Second spindle	Max. spindle speed	5000 rpm
	Spindle motor (40%ED)	22 kW (30 HP)
	Spindle motor (cont. rating)	15 kW (20 HP)
Turret	Tool shank height	1 "
	Boring bar shank diameter	Φ2 "
Rotary tool spindle	Max. spindle speed	5000 rpm
	Max. torque (40%ED)	34.4 ft-lbs
	Spindle motor (40%ED)	5.5 kW (7.5 HP)
	Spindle motor (cont. rating)	3.7 kW (5 HP)
Travel	X-axis	11 "
	Y-axis	±2"
	Z-axis*	19 "
Rapid traverse rate	X-axis	1378 IPM
	Y-axis	591 IPM
	Z- axis	1654 IPM
Machine size	Width × Length (MAZATROL SmoothG)	141 " × 85 "
	Height	81 "
	Machine weight	24691 lbs
* Z2 : 20.67"		