

POWER MASTER Universal

3000U		
Universal	Universal type	3000U
Capacity	Max. machining diameter	Φ33 "
	Max. machining length	118 "
	Swing over bed	34 "
Spindle	Max. spindle speed	1200 rpm
	Max. torque (40%ED)	5369 ft-lbs
	Spindle motor (40%ED)	45 kW (60 HP)
	Spindle motor (cont. rating)	37 kW (50 HP)
Turret	Turret type	8-tool turret
Travel	X-axis	26 "
	Z- axis	121 "
Rapid traverse rate	X-axis	472 IPM
	Z- axis	472 IPM
Tailstock	Tailstock center	MT No.5
Machine size	Width × Length (MAZATROL SmoothC)	275 " × 109 "
	Height	85 "
	Machine weight	32838 lbs
4000U		
Universal	Universal type	4000U
Capacity	Max. machining diameter	Φ33 "
	Max. machining length	158 "
	Swing over bed	34 "
Spindle	Max. spindle speed	1200 rpm
	Max. torque (40%ED)	5369 ft-lbs
	Spindle motor (40%ED)	45 kW (60 HP)
	Spindle motor (cont. rating)	37 kW (50 HP)
Turret	Turret type	8-tool turret
Travel	X-axis	26 "
	Z- axis	161 "
Rapid traverse rate	X-axis	472 IPM
	Z- axis	472 IPM
Tailstock	Tailstock center	MT No.5
Machine size	Width × Length (MAZATROL SmoothC)	315 " × 109 "
	Height	85 "
	Machine weight	35042 lbs