

QTE-200 SG

300U	Universal type	
Universal	Universal type	300U
Capacity	Max. machining diameter	Φ350 mm
	Max. machining length	285 mm
Spindle	Chuck size	8 "
	Max. spindle speed	5000 min-1
	Max. torque (40%ED)	116.9 N·m
	Spindle motor (40%ED)	15 kW (20 HP)
	Spindle motor (cont. rating)	11 kW (15 HP)
Turret	Tool storage capacity	8
	Tool shank height	25 mm
	Boring bar shank diameter	Φ40 mm
Travel	X-axis	195 mm
	Z- axis	325 mm
Rapid traverse rate	X-axis	30000 mm/min
	Z- axis	30000 mm/min
Tailstock	Tailstock center	MT No.4
Machine size	Width × Length (MAZATROL SmoothEz)	1900 mm × 1590 mm
	Height	1700 mm
	Machine weight	3400 kg
500U		
Universal	Universal type	500U
Capacity	Max. machining diameter	Φ350 mm
	Max. machining length	520 mm
Spindle	Chuck size	8 "
	Max. spindle speed	5000 min-1
	Max. torque (40%ED)	116.9 N·m
	Spindle motor (40%ED)	15 kW (20 HP)
	Spindle motor (cont. rating)	11 kW (15 HP)
Turret	Tool storage capacity	8
	Tool shank height	25 mm
	Boring bar shank diameter	Φ40 mm
Travel	X-axis	195 mm
	Z- axis	560 mm
Rapid traverse rate	X-axis	30000 mm/min
	Z- axis	30000 mm/min
Tailstock	Tailstock center	MT No.5
Machine size	Width × Length (MAZATROL SmoothEz)	2200 mm × 1590 mm
	Height	1700 mm
	Machine weight	3700 kg