

QUICK TURN 200MB

500U	Universal type	500U
Universal	Universal type	500U
Capacity	Max. machining diameter	Φ380 mm
	Max. machining length	541 mm
	Chuck size	8 "
	Max. spindle speed	5000 min-1
	Max. torque (40%ED)	140 N·m
	Spindle motor (40%ED)	15 kW (20 HP)
Spindle	Spindle motor (cont. rating)	11 kW (15 HP)
	Turret type	12 positon drum turret (VDI)
	Tool storage capacity	12
	Tool shank height	25 mm
Turret	Boring bar shank diameter	Φ40 mm
	Max. spindle speed	5000 min-1
	Max. torque (40%ED)	47 N·m
	Spindle motor (40%ED)	5.5 kW (7.5 HP)
Rotary tool spindle	Spindle motor (cont. rating)	3.7 kW (5 HP)
	X-axis	234 mm
Travel	Z- axis	625 mm
	X-axis	30000 mm/min
	Z- axis	33000 mm/min
Rapid traverse rate	C-axis	555 min-1
Tailstock	Tailstock center	MT No.5
	Width × Length (MAZATROL SmoothG)	2760 mm × 1845 mm
	Height	1857 mm
Machine size	Machine weight	5500 kg
	Height	1857 mm
	Machine weight	5900 kg
1000U		
Universal	Universal type	1000U
Capacity	Max. machining diameter	Φ380 mm
	Max. machining length	1047 mm
	Chuck size	8 "
	Max. spindle speed	5000 min-1
	Max. torque (40%ED)	140 N·m
	Spindle motor (40%ED)	15 kW (20 HP)
Spindle	Spindle motor (cont. rating)	11 kW (15 HP)
	Turret type	12 positon drum turret (VDI)
	Tool storage capacity	12
	Tool shank height	25 mm
Turret	Boring bar shank diameter	Φ40 mm
	Max. spindle speed	5000 min-1
	Max. torque (40%ED)	47 N·m
	Spindle motor (40%ED)	5.5 kW (7.5 HP)
Rotary tool spindle	Spindle motor (cont. rating)	3.7 kW (5 HP)
	X-axis	234 mm
Travel	Z- axis	1090 mm
	X-axis	30000 mm/min
	Z- axis	33000 mm/min
Rapid traverse rate	C-axis	555 min-1
Tailstock	Tailstock center	MT No.5
	Width × Length (MAZATROL SmoothG)	3550 mm × 1995 mm
	Height	1857 mm
Machine size	Machine weight	6200 kg