

QUICK TURN 250MSY

500U		
Universal	Universal type	20 "
Capacity	Max. swing	Φ27 "
	Max. machining diameter	Φ15 "
	Max. machining length	21 "
	Bar work capacity	Φ3 "
Spindle	Chuck size	10 "
	Max. spindle speed	4000 rpm
	Spindle motor (30 min. rating)	26 kW (35 HP)
Second spindle	Chuck size	6 "
	Max. spindle speed	6000 rpm
	Spindle motor (30 min. rating)	11 kW (15 HP)
Turret	Tool storage capacity	12
Travel	X-axis	9 "
	Y-axis	4 "
	Z- axis	23 "
	W-axis (Second spindle)	23 "

1000U		
Universal	Universal type	40 "
Capacity	Max. swing	Φ27 "
	Max. machining diameter	Φ15 "
	Max. machining length	36 "
	Bar work capacity	Φ3 "
Spindle	Chuck size	10 "
	Max. spindle speed	4000 rpm
	Spindle motor (30 min. rating)	26 kW (35 HP)
Second spindle	Chuck size	6 "
	Max. spindle speed	6000 rpm
	Spindle motor (30-min. rating)	11 kW (15 HP)
Turret	Tool storage capacity	12
Travel	X-axis	9 "
	Y-axis	4 "
	Z- axis	43 "
	W-axis (Second spindle)	37 "