

QUICK TURN 300

650U	Universal type	500U
Universal	Universal type	650U
Capacity	Max. machining diameter	Φ420 mm
	Max. machining length	662 mm
	Chuck size	10 "
	Max. spindle speed	4000 min-1
	Max. torque (40%ED)	252 N·m
	Spindle motor (40%ED)	26 kW (35 HP)
Spindle	Spindle motor (cont. rating)	22 kW (30 HP)
	Tool storage capacity	12
	Tool shank height	25 mm
Turret	Boring bar shank diameter	Φ50 mm
	X-axis	240 mm
Travel	Z- axis	710 mm
	X-axis	30000 mm/min
Rapid traverse rate	Z- axis	33000 mm/min
Tailstock	Tailstock center	MT No.5
	Width × Length (MAZATROL SmoothG)	3050 mm × 1910 mm
	Height	1900 mm
Machine size	Machine weight	5800 kg
1250U		
Universal	Universal type	1250U
Capacity	Max. machining diameter	Φ420 mm
	Max. machining length	1282 mm
	Chuck size	10 "
	Max. spindle speed	4000 min-1
	Max. torque (40%ED)	252 N·m
	Spindle motor (40%ED)	26 kW (35 HP)
Spindle	Spindle motor (cont. rating)	22 kW (30 HP)
	Tool storage capacity	12
	Tool shank height	25 mm
Turret	Boring bar shank diameter	Φ50 mm
	X-axis	240 mm
Travel	Z- axis	1314 mm
	X-axis	30000 mm/min
Rapid traverse rate	Z- axis	33000 mm/min
Tailstock	Tailstock center	MT No.5
	Width × Length (MAZATROL SmoothG)	3770 mm × 1910 mm
	Height	1900 mm
Machine size	Machine weight	6600 kg
1500U		
Universal	Universal type	1500U
Capacity	Max. machining diameter	Φ420 mm
	Max. machining length	1597 mm
	Chuck size	10 "
	Max. spindle speed	4000 min-1
	Max. torque (40%ED)	252 N·m
	Spindle motor (40%ED)	26 kW (35 HP)
Spindle	Spindle motor (cont. rating)	22 kW (30 HP)
	Tool storage capacity	12
	Tool shank height	25 mm
Turret	Boring bar shank diameter	Φ50 mm
	X-axis	240 mm
Travel	Z- axis	1640 mm
	X-axis	30000 mm/min
Rapid traverse rate	Z- axis	33000 mm/min
Tailstock	Tailstock center	MT No.5
	Width × Length (MAZATROL SmoothG)	4500 mm × 1910 mm
	Height	1900 mm
Machine size	Machine weight	7000 kg