

QUICK TURN 300MB

650U	Universal type	500U
Universal	Universal type	650U
Capacity	Max. machining diameter	Φ420 mm
	Max. machining length	652 mm
	Chuck size	10 "
	Max. spindle speed	4000 min-1
	Max. torque (40%ED)	252 N·m
	Spindle motor (40%ED)	26 kW (35 HP)
	Spindle motor (cont. rating)	22 kW (30 HP)
	Turret type	12 positon drum turret (VDI)
	Tool storage capacity	12
	Tool shank height	25 mm
	Boring bar shank diameter	Φ50 mm
	Max. spindle speed	5000 min-1
	Max. torque (40%ED)	54 N·m
	Spindle motor (40%ED)	7.5 kW (10 HP)
	Spindle motor (cont. rating)	5.5 kW (8 HP)
	X-axis	270 mm
	Z- axis	680 mm
	X-axis	30000 mm/min
	Z- axis	33000 mm/min
	C-axis	555 min-1
	Tailstock center	MT No.5
	Width × Length (MAZATROL SmoothG)	3355 mm × 2100 mm
	Height	2175 mm
	Machine weight	8800 kg
1250U		
Universal	Universal type	1250U
Capacity	Max. machining diameter	Φ420 mm
	Max. machining length	1247 mm
	Chuck size	10 "
	Max. spindle speed	4000 min-1
	Max. torque (40%ED)	252 N·m
	Spindle motor (40%ED)	26 kW (35 HP)
	Spindle motor (cont. rating)	22 kW (30 HP)
	Turret type	12 positon drum turret (VDI)
	Tool storage capacity	12
	Tool shank height	25 mm
	Boring bar shank diameter	Φ50 mm
	Max. spindle speed	5000 min-1
	Max. torque (40%ED)	54 N·m
	Spindle motor (40%ED)	7.5 kW (10 HP)
	Spindle motor (cont. rating)	5.5 kW (8 HP)
	X-axis	270 mm
	Z- axis	1280 mm
	X-axis	30000 mm/min
	Z- axis	33000 mm/min
	C-axis	555 min-1
	Tailstock center	MT No.5
	Width × Length (MAZATROL SmoothG)	3915 mm × 2100 mm
	Height	2175 mm
	Machine weight	9450 kg