

QUICK TURN 300MY

1500U	Universal type	
Universal	Universal type	1500U
Capacity	Max. machining diameter	Φ430 mm
	Max. machining length	1593 mm
Spindle	Chuck size	10 "
	Max. spindle speed	4000 min-1
	Max. torque (40%ED)	252 N·m
	Spindle motor (40%ED)	26 kW (35 HP)
	Spindle motor (cont. rating)	22 kW (30 HP)
	Tool storage capacity	12
Turret	Tool shank height	25 mm
	Boring bar shank diameter	Φ50 mm
Rotary tool spindle	Max. spindle speed	5000 min-1
	Max. torque (40%ED)	54 N·m
	Spindle motor (40%ED)	7.5 kW (10 HP)
	Spindle motor (cont. rating)	5.5 kW (8 HP)
Travel	X-axis	270 mm
	Y-axis	150 mm (±75 mm)
	Z- axis	1620 mm
Rapid traverse rate	X-axis	30000 mm/min
	Y-axis	15000 mm/min
	Z- axis	33000 mm/min
	C-axis	555 min-1
Tailstock	Tailstock center	MT No.5
Machine size	Width × Length (MAZATROL SmoothG)	4270 mm × 2100 mm
	Height	2175 mm
	Machine weight	8800 kg