

QUICK TURN 350MA

650U	Universal type	
Universal	Universal type	650U
Capacity	Max. machining diameter	Φ420 mm
	Max. machining length	614 mm
	Chuck size	12 "
	Max. spindle speed	3300 min-1
	Max. torque (40%ED)	724 N·m
	Spindle motor (40%ED)	30 kW (40 HP)
Spindle	Spindle motor (cont. rating)	22 kW (30 HP)
	Turret type	12 positon drum turret (bolt-on)
	Tool storage capacity	12
	Tool shank height	25 mm
Turret	Boring bar shank diameter	Φ50 mm
	Max. spindle speed	5000 min-1
	Max. torque (40%ED)	54 N·m
	Spindle motor (40%ED)	7.5 kW (10 HP)
Rotary tool spindle	Spindle motor (cont. rating)	5.5 kW (8 HP)
	X-axis	265 mm
Travel	Z- axis	730 mm
	X-axis	30000 mm/min
	Z- axis	33000 mm/min
Rapid traverse rate	C-axis	555 min-1
Tailstock	Tailstock center	MT No.5
	Width × Length (MAZATROL SmoothG)	3050 mm × 1910 mm
	Height	1900 mm
Machine size	Machine weight	6400 kg
1250U		
Universal	Universal type	1250U
Capacity	Max. machining diameter	Φ420 mm
	Max. machining length	1234 mm
	Chuck size	12 "
	Max. spindle speed	3300 min-1
	Max. torque (40%ED)	724 N·m
	Spindle motor (40%ED)	30 kW (40 HP)
Spindle	Spindle motor (cont. rating)	22 kW (30 HP)
	Turret type	12 positon drum turret (bolt-on)
	Tool storage capacity	12
	Tool shank height	25 mm
Turret	Boring bar shank diameter	Φ50 mm
	Max. spindle speed	5000 min-1
	Max. torque (40%ED)	54 N·m
	Spindle motor (40%ED)	7.5 kW (10 HP)
Rotary tool spindle	Spindle motor (cont. rating)	5.5 kW (8 HP)
	X-axis	265 mm
Travel	Z- axis	1350 mm
	X-axis	30000 mm/min
	Z- axis	33000 mm/min
Rapid traverse rate	C-axis	555 min-1
Tailstock	Tailstock center	MT No.5
	Width × Length (MAZATROL SmoothG)	3770 mm × 1910 mm
	Height	1900 mm
Machine size	Machine weight	7200 kg