

QUICK TURN 350MB

650U	Universal type	
Universal	Universal type	650U
Capacity	Max. machining diameter	Φ420 mm
	Max. machining length	604 mm
Spindle	Chuck size	12 "
	Max. spindle speed	3300 min-1
	Max. torque (40%ED)	724 N·m
	Spindle motor (40%ED)	30 kW (40 HP)
	Spindle motor (cont. rating)	22 kW (30 HP)
Turret	Turret type	12 positon drum turret (VDI)
	Tool storage capacity	12
	Tool shank height	25 mm
	Boring bar shank diameter	Φ50 mm
Rotary tool spindle	Max. spindle speed	5000 min-1
	Max. torque (40%ED)	54 N·m
	Spindle motor (40%ED)	7.5 kW (10 HP)
	Spindle motor (cont. rating)	5.5 kW (8 HP)
Travel	X-axis	270 mm
	Z- axis	690 mm
Rapid traverse rate	X-axis	30000 mm/min
	Z- axis	33000 mm/min
	C-axis	555 min-1
Tailstock	Tailstock center	MT No.5
Machine size	Width × Length (MAZATROL SmoothG)	3355 mm × 2100 mm
	Height	2175 mm
	Machine weight	9000 kg
1250U		
Universal	Universal type	1250U
Capacity	Max. machining diameter	Φ420 mm
	Max. machining length	1199 mm
Spindle	Chuck size	12 "
	Max. spindle speed	3300 min-1
	Max. torque (40%ED)	724 N·m
	Spindle motor (40%ED)	30 kW (40 HP)
	Spindle motor (cont. rating)	22 kW (30 HP)
Turret	Turret type	12 positon drum turret (VDI)
	Tool storage capacity	12
	Tool shank height	25 mm
	Boring bar shank diameter	Φ50 mm
Rotary tool spindle	Max. spindle speed	5000 min-1
	Max. torque (40%ED)	54 N·m
	Spindle motor (40%ED)	7.5 kW (10 HP)
	Spindle motor (cont. rating)	5.5 kW (8 HP)
Travel	X-axis	270 mm
	Z- axis	1285 mm
Rapid traverse rate	X-axis	30000 mm/min
	Z- axis	33000 mm/min
	C-axis	555 min-1
Tailstock	Tailstock center	MT No.5
Machine size	Width × Length (MAZATROL SmoothG)	3915 mm × 2100 mm
	Height	2175 mm
	Machine weight	9650 kg