

QUICK TURN 400

1000U	Universal type	
Universal	Universal type	1000U
Capacity	Max. machining diameter	Φ580 mm
	Max. machining length	1024 mm
Spindle	Chuck size	12 "
	Max. spindle speed	2500 min-1
	Max. torque (40%ED)	1848 N·m
	Spindle motor (40%ED)	37 kW (50 HP)
	Spindle motor (cont. rating)	30 kW (40 HP)
Turret	Tool storage capacity	12
	Tool shank height	32 mm
	Boring bar shank diameter	Φ50 mm
Travel	X-axis	320 mm
	Z- axis	1070 mm
Rapid traverse rate	X-axis	30000 mm/min
	Z- axis	30000 mm/min
Tailstock	Tailstock center	MT No.5
Machine size	Width × Length (MAZATROL SmoothG)	3820 mm × 2313 mm
	Height	2040 mm
	Machine weight	9900 kg
2000U		
Universal	Universal type	2000U
Capacity	Max. machining diameter	Φ580 mm
	Max. machining length	2074 mm
Spindle	Chuck size	12 "
	Max. spindle speed	2500 min-1
	Max. torque (40%ED)	1848 N·m
	Spindle motor (40%ED)	37 kW (50 HP)
	Spindle motor (cont. rating)	30 kW (40 HP)
Turret	Tool storage capacity	12
	Tool shank height	32 mm
	Boring bar shank diameter	Φ50 mm
Travel	X-axis	320 mm
	Z- axis	2120 mm
Rapid traverse rate	X-axis	30000 mm/min
	Z- axis	30000 mm/min
Tailstock	Tailstock center	MT No.5
Machine size	Width × Length (MAZATROL SmoothG)	4930 mm × 2313 mm
	Height	2040 mm
	Machine weight	11700 kg