

SLANT TURN 500M

C		
Universal	Universal type	Chucker
Capacity	Max. machining diameter	Φ36 "
	Max. machining length	43 "
Spindle	Chuck size	18 "
	Max. spindle speed	1600 rpm
	Max. torque (Low speed winding: Low range)	5163 ft-lbs
	Spindle motor (30 min. rating)	45 kW (60 HP)
	Spindle motor (cont. rating)	37 kW (50 HP)
	Spindle bore	Φ7 "
Turret	Tool storage capacity	12
	Tool shank height	1 "
	Boring bar shank diameter	Φ2 "
Rotary tool spindle	Max. spindle speed	4000 rpm
	Max. torque (4 min. rating)	70 ft-lbs
	Spindle motor (4 min. rating)	7.5 kW (10 HP)
	Spindle motor (cont. rating)	1.5 kW (2 HP)
Travel	X-axis	18 "
	Z- axis	46 "
Rapid traverse rate	X-axis	787 IPM
	Z- axis	945 IPM
Machine size	Width × Length (MAZATROL SmoothG)	224 " × 96 "
	Height	103 "
	Machine weight	30423 lbs
1000U		
Universal	Universal type	1000U
Capacity	Max. machining diameter	Φ36 "
	Max. machining length	43 "
Spindle	Chuck size	18 "
	Max. spindle speed	1600 rpm
	Max. torque (Low speed winding: Low range)	5163 ft-lbs
	Spindle motor (30 min. rating)	45 kW (60 HP)
	Spindle motor (cont. rating)	37 kW (50 HP)
	Spindle bore	Φ7 "
Turret	Tool storage capacity	12
	Tool shank height	1 "
	Boring bar shank diameter	Φ2 "
Rotary tool spindle	Max. spindle speed	4000 rpm
	Max. torque (4 min. rating)	70 ft-lbs
	Spindle motor (4 min. rating)	7.5 kW (10 HP)
	Spindle motor (cont. rating)	1.5 kW (2 HP)
Travel	X-axis	18 "
	Z- axis	46 "
Rapid traverse rate	X-axis	787 IPM
	Z- axis	945 IPM
Tailstock	Travel	34 "
	Tailstock center	MT No.6
Machine size	Width × Length (MAZATROL SmoothG)	224 " × 96 "
	Height	103 "
	Machine weight	33289 lbs