

TURNING CENTER M-5

2000U		
Universal	Universal type	2000U
Capacity	Max. swing	Φ24 "
	Max. machining diameter	Φ23 "
	Swing over carriage	Φ13 "
	Max. machining length	76 "
	Distance from spindle face to turret face	5 " to 86 "
	Max. weight capacity: Chuck work	9480 lbs
	Bar work capacity	Φ7 "
Spindle	Chuck size	15 "
	Max. spindle speed	1000 rpm
	Max. torque (40%ED)	1179 ft-lbs
	Spindle motor (40%ED)	22 kW (30 HP)
	Spindle bore	Φ181 "
Travel	X-axis	22 "
	Z- axis	81 "
Rapid traverse rate	X-axis	472 IPM
	Z- axis	551 IPM
Tailstock	Travel	4 "
	Tailstock stroke	5 "
	Tailstock center	MT No.5
Machine size	Width × Length (MAZATROL SmoothC)	200 " × 102 "
	Height	81 "
	Machine weight	14771 lbs
3000U		
Universal	Universal type	3000U
Capacity	Max. swing	Φ24 "
	Max. machining diameter	Φ23 "
	Swing over carriage	Φ13 "
	Max. machining length	116 "
	Distance from spindle face to turret face	5 " to 126 "
	Max. weight capacity: Chuck work	9480 lbs
	Bar work capacity	Φ7 "
Spindle	Chuck size	15 "
	Max. spindle speed	1000 rpm
	Max. torque (40%ED)	1179 ft-lbs
	Spindle motor (40%ED)	22 kW (30 HP)
	Spindle bore	Φ7 "
Travel	X-axis	22 "
	Z- axis	121 "
Rapid traverse rate	X-axis	472 IPM
	Z- axis	551 IPM
Tailstock	Travel	100 "
	Tailstock stroke	130 "
	Tailstock center	MT No.5
Machine size	Width × Length (MAZATROL SmoothC)	240 " × 102 "
	Height	81 "
	Machine weight	16976 lbs